

HOLLOW SECTIONS

- **Plain round bars** (straightened from wire rod coil and rolled)

Dimensions: * Ø 6,0; 8,0 (straightened from wire rod SAE1006, SAE1008, S235),

* Ø 10, 12, 14, 16, 18, 20, 22, 24, 25, 26, 27, 28, 30, 32 (rolled).

Grades: S235JR+AR, S355J2 acc. EN 10025-2:2004 (other steel grades on request).

Length: 6000 mm and 12 000mm, tol. -0/+200mm.

Bundle weight: approximately 2,5T.

Inspection certificate. EN 10204/3.1 + CE.

- **Square bars**

Dimensions: 10x10, 12x12, 14x14, 16x16, 18x18, 20x20.

Grades: S235JR+AR, S355J2 acc. EN 10025-2:2004 (other steel grades on request).

Bundle weight: approximately 2,0T.

- **Flat bars**

Dimensions: 20-100x5-20; 55-100x25-40; 110-120x8-20.

Grades: S235JR, S355J2, 50G, grade. A, A36.

It is possible to have the additional certification of the goods from the following international classification societies: DNV, LRS, BV.

- **Equal and unequal angles**

Dimensions: 20x20x3, 4; 25x25x3,4,5; 35x35x3,4,5; 40x40x3,4,5; 45x45x4,5; 50x50x4,5,6; 30x20x3,4; 60x40x5,6.

Grades: S235JR, S355J2.